	6	5	4	ቑ	3	
D	NOTES: 1. ALL DIMENSIONS FOR REFERENCE ONLY 2. REFER TO AIR LOGIC'S POLYSULFONE APPLICATION GUIDE 3. TUBE RETENTION PRESSURE SUBJECT TO TUBING DIMENSION AND STIFFNESS					
С			DEBOSS	Ø.25 [Ø6.4]	Ø.030 [Ø0.76]	
Å		.030 .33 TYP	Ø.104 TYP. [Ø2.64]			
В	-	_ 1.02			TIONS FOR 1/16" [1.6] I.D. TUI RST BARB FREE OF PARTING LI	
	PRODUCT SPECIFICATIONS		AIR-LOGIC 5102 DOUGLAS AVE RACINE, WI 53402 PHONE: (262) 639-9035 FAX: (262) 639-5996 WEB: AIR-LOGIC.COM		TERMS THIS DI NO REP	
A	COLOR(S)	GASES, LIQUIDS, NOTE 2		PART/DRAWING NO.: F2815301B80		PARTIC
	MEDIA MAX INLET PRESSURE					AND CC
	TYPICAL TUBE RETENTION PRESSURE 125 PSI, [8.6 BAR], NOTE 3		DESCRIPTION: Ø.030" ORIFICE RESTRICTOR, 1/16" BARBS			
	-OW COEFFICIENT (Cv) 0.0245				D	
	NOMINAL ORIFICE DIAMETER	Ø.030, [Ø0.76]				TOLE
	WETTED MATERIALS	POLYSULFONE		REVISION: B	DRAWN: 2/24/2021	
	RECOMMENDED SYSTEM FILTRATION			SCALE: 4 : 1	SHEET SIZE: B	
	6	5	4	4	3	

