	6	5	4	\forall	3	
D	NOTES: 1. ALL DIMENSIONS FOR REFER 2. REFER TO AIR LOGIC'S POLY 3. TUBE RETENTION PRESSURE		ID STIFFNESS			
						0
C		FILTER SIZ	ZE DEBOSS			
Ľ				—Ø.25 [Ø6.		
A		43µm			Ø.104 TYP.	33TYP
В		N FOR 1/16" [1.6] I.D. TUBE, – ARB FREE OF PARTING LINE			[Ø2.64]	[8.3]
	PRODUCT SPECIFICATIONS					
	COLOR	LIGHT BLUE			® DIVISION OF KNAPP MFG, INC. E, WI 53402	TERMS THIS D
	FILTER AREA	0.027 in^2, [17.7 mm^2]		PHONE: (262) 639-9035 FA	X: (262) 639-5996 WEB: AIR-LOGIC.COM	NO REF
	FILTER SIZE	43 MICRON				AND CC
A		GASES, LIQUIDS, NOTE 2		F95043B80 DESCRIPTION:		D
	MAX INLET PRESSURE	125 PSI, [8.6 BAR]	2	INLINE FILTER, 43 MICRO) N, 1/16" BARBS	
	TYPICAL TUBE RETENTION PRES MINIMUM INNER DIAMETER	SURE 125 PSI, [8.6 BAR], NOTE Ø.045, [Ø1.14]	<u>с</u>			TOLE
	WETTED MATERIALS	POLYSULFONE, STAINLES	S STEFI	REVISION: B	DRAWN: 2/24/2021	
	6	5	4	SCALE: 5 : 1	SHEET SIZE: B 3	
	-	-	· ·	Т	-	

